

Spit 216 Dry Wall Screwdriver



Extremely lightweight and compact

The universal drywall screw gun is particularly suitable for drywall fixing.

Product Advantages

- Adjustable depth stop
- Interchangeable bit holder
- Lock-on button for continuous operation
- Forward / reverse selector
- Equipped with electronic speed adjustment for precision work
- 6 metre electrical cable and can be used from floor to ceiling without the need of an extension cable

Noise / Vibration Information

Measured values determined according to EN 50 144 50144. Typically the A - weight noise levels of the tool are:

Sound pressure level	77 dB (A)
Work place emission value	73dB (A)
Sound power level	88 dB (A)
Wear ear and eye protection	

Vibration: The typical weighted acceleration does not exceed 2.5m/s²

Specification

Machine weight	1.1kg
Voltage	110V
Amperage	4.9A
Frequency	50 - 60Hz
Power input	500W
Rotation speed - unload	0 - 3,000rpm
Torque at rated load	5Nm
Tool holder	1 / 4"
Clamping collar diameter	43mm
Cable length	6m

Applications



- Plasterboard or fibre-cement board onto metal stud and track
- Metal support onto steel

Product Range - Spit 216 Dry Wall Screwdriver

Eurocode	Description	Box Qty
010098	Spit 216 110V	1

Kit includes: Spit 216 in shock proof case, lubricating oil and instruction manual

